1043

AIR AND OXYGEN GASIFICATION SIMULATION ANALYSIS OF SAWDUST

by

Dillibabu VENUGOPAL^{a*}, Lakshmanan THANGAVELU^b, and Natarajan ELUMALAI^c

 ^a Department of Mechanical Engineering, RMK College of Engineering and Technology, Anna University, Chennai, India
 ^b Department of Mechanical Engineering, S. A Engineering College, Anna University, Chennai, India
 ^c Department of Mechanical Engineering, Institute for Energy Studies, Anna University, Chennai, India

> Original scientific paper https://doi.org/10.2298/TSCI170613102V

Gasification is the conversion process of low-grade solid fuel into gaseous fuel by thermochemical reactions. In this paper air gasification and oxygen gasification simulation of sawdust is carried out using FACTSAGE 6.3 software. The effect of temperature and equivalence ratio, ϕ , on producer gas composition is analysed. Combustible gas compositions (H₂, CO, and CH₄) are found out at different operating conditions for air and oxygen gasification separately. Temperature range is 200-1200 °C and ϕ value varied from 0.3-0.6. Gas heating values (higher and lower heating value) carbon conversion efficiency and cold gas efficiency are calculated. In air gasification, maximum higher heating value of 5.96 MJ/Nm³ is reached at 700 °C for $\phi = 0.3$ and in oxygen gasification, 9.85 MJ/Nm³ is attained at 800 °C and $\phi = 0.3$. The maximum cold gas efficiency of 84.37 and 84.73% reached by air and oxygen gasification, respectively, at 1200 °C for $\phi = 0.3$.

Key words: sawdust, air gasification, oxygen gasification, simulation, FACTSAGE

Introduction

Gasification is an old technique practised in the early 19th century to illuminate street with coal gas. The energy crisis in 1970 gave re-birth to gasification technology and demand for clean energy stimulates the research and development. Gasification is the conversion process of carbonaceous material into combustible gas by partial oxidation at high temperature [1]. Heat and combustible gases are the main products of gasification, ash, char, tar and non-condensable gases are by-products. Char is the carbonaceous solid residue of biomass, tar is a mixture of phenol, polycyclic aromatic hydrocarbons, and heterocyclic hydrocarbons [2]. The main gaseous products formed during gasification are CO, CO₂, hydrogen, CH₄, water vapour, and nitrogen from the air [3, 4]. During gasification process, fuel undergoes four stages namely drying, pyrolysis, gasification and combustion [5, 6]. Biomass and coal are the main fuel for the gasification process.

^{*} Corresponding author, e-mail: babudilli8@gmail.com

Biomass includes wood, agricultural residues, municipal solid waste and wastes from food processing and many more. Biomass is an attractive fuel in the developed country, it is renewable, low in sulphur content and CO₂ neutral [7]. It is utilised for chemical raw materials production, power generation and production of alternate fuel [8]. Direct combustion is the traditional way of utilising biomass and it causes more pollution and has low energy conversion efficiency [3, 4]. Electricity can be generated with single fuel or mixture of fuels by gasification-based power generation technique, has higher efficiency than conventional pulverised fuel combustion method [9]. Biomass contains volatiles, fixed carbon, ash and moisture, on heating moisture removed around 120 °C. Devolatilisation takes place up to 350 °C and char gasification occurs above 350 °C [10]. All type of biomass has more oxygen and hydrogen content and less carbon than coal, it is indicated by higher volatile and moisture content [7]. Due to high reactivity, biomass releases more volatile matter which improves oxidation and gasification reactions [11]. Gasification is an endothermic process, heat is supplied by partial oxidation of fuel in case of auto-thermal and external heat is supplied for allothermal gasification [10]. Operating temperature of gasifier varies from 200-1200 °C and pressure ranges from atmospheric pressure to 2.4 MPa. Biomass air gasification produces gases with lower heating value (LHV) of 4-6 MJ/Nm³ with 8-14% of H₂ but highly diluted with N₂ [12, 13]. Oxygen gasification provides the medium gas heating value of 10-12 MJ/Nm³ and free from tar, the steam gasification heating value is in the range of 10-16 MJ/Nm^3 with 30-60% of H₂ content and superior carbon conversion [14-16].

Shayan et al. [17] studied gasification of wood and paper by stoichiometric equilibrium model with the gasifying mediums - air, O_2 enriched air, O_2 , and steam. The calorific value of gas, energy efficiency, exergy efficiency, and exergy destruction are found. For wood, the gas calorific value of 5.3 and 11.2 MJ/Nm³ are obtained in air and steam gasification, respectively. Shweta and Pratik [18] studied the effect of moisture content, steam to biomass ratio and equivalence ratio on gas composition in a downdraft gasifier for combined air-steam gasification. Equilibrium modelling results are validated with experimental values. Gas composition, calorific values and cold gas efficiencies are calculated. Karl et al. [19] studied gasification of switchgrass in oxygen and steam blown fluidised bed gasifier, for equivalence ratio 0.21-0.38 and temperature up to 900 °C. An equilibrium model is developed by ASPEN PLUS software, gas composition (H₂, CO, CO₂, CH₄, C₂H₆, C₂H₄, C₂H₂, HCN, and NH₃), heavy tar content, char content, gas yield, higher heating value (HHV), carbon conversion efficiency (CCE), and cold gas efficiency (CGE) are calculated. Niu et al. [20] gasified municipal solid waste (paper, wood, textile, and kitchen garbage) with O₂ in fixed bed gasifier. Gas composition, char, tar and gas lower heating value are found for 700-900 °C and $\phi = 0.14-0.32$. The LHV of gas is in the range of 6-10 MJ/Nm³. In the present study, maximum LHV of 9.24 MJ/Nm³ is obtained in oxygen gasification at 1200 °C for $\phi = 0.3$.

In the present work, gasification of sawdust is carried out by FACTSAGE 6.3 software for air and oxygen mediums. Non-stoichiometric equilibrium model based on Gibbs free energy minimisation with Lagrange multiplier iterative method is used to find out the equilibrium composition of end products for temperature range 200-1200 °C and ϕ value 0.3-0.6. The objective function of the model is given by eq. (1), it is subjected to mass balance and non-negativity of the number of moles to find end composition.

$$\frac{G}{RT} = \sum_{j=1}^{n} n_j \left(\frac{G^0}{RT} + \ln \frac{n_j}{\Sigma n_j} \right)$$
(1)

1044

where *G* [kJ] is the total Gibbs energy, $G^0 - [kJ]$ the Gibbs energy of pure component, $R - [kJkmol^{-1}K^{-1}]$ the universal gas constant, and n_j – the number of moles of component *j*.

To validate the model, simulation results of rice husk air gasification and steam gasification are compared with experimental work of Karmakar *et al.* [21] and Loha *et al.* [22], respectively. The root mean square (RMS) values are calculated using eq. (2), Karmakar *et al.* [21] used 50 kg per hour bubbling fluidised bed gasifier and sand as bed material with the mean diameter of 0.334 mm. The reactor is made up of carbon steel, cylindrical in shape with an inner diameter of 0.5 m and 1 m in height. Loha *et al.* [22] used laboratory scale fluidised bed gasifier of 50 mm diameter and 1200 mm in height. Sand used as bed material and steam as a gasifying agent, heat is supplied by an electric furnace.

$$RMS = \sqrt{\frac{\sum_{J}^{N} (\text{Experiment} - \text{Simulation})^{2}}{N}}$$
(2)

where N is the number of gas components.

Methodology

Elemental composition of fuel, the quantity of air, temperature and pressure of gasification are the input details for simulation. Basic elements of sawdust are C, H, O, N, and S; nitrogen and sulphur are generally neglected in gasification process because of its low content in fuels [10]. In order to analyze the effect of temperature on gas composition, temperature varied from 200 °C to 1200 °C by 100 °C, equivalence ratio value varied from 0.3 to 0.6 by 0.05 for both air and oxygen gasification. The lower limit of ϕ value is decided by the minimum quantity of gasifying medium required to burn the fuel and to produce sufficient heat for endothermic reactions [23]. When ϕ value < 0.3, it is difficult to run the gasifier due to insufficient gasifying medium and if ϕ > 0.6, it leads to combustion instead of gasification. Calculated sawdust stoichiometric oxygen to fuel ratio and air to fuel ratio are 1.22 and 5.29, respectively. Combustible gas composition (H₂, CO, and CH₄), gas heating values (HHV and LHV), CCE, CGE are found. Proximate and ultimate analysis details of sawdust and rice husk are shown in tab. 1.

Table 1. Proximate and ultimate analysis of sawdust and rice husk

S. no	Fuel	Proximate analysis				Ultimate analysis					
		Volatile matter	Fixed carbon	Moisture	Ash	С	Н	N	0	S	
1	Sawdust [24]	76.1	8.9	14.6	0.40	44.96	5.83	3.10	45.5	0.61	
2	Rice husk [21]	55.54	14.99	9.95	19.52	38.43	2.97	0.49	36.36	0.07	
		Combustible									
3	Rice husk [22]	70.53		11.5	8.5	49.07	3.79	0.63	46.42	0.09	

Method of data processing

The HHV of the gas mixture is calculated from final gas composition given by Xiao *et al.* [25]:

 $HHV = [(H_2\% \times 30.52 + CO\% \times 30.18 + CH_4\% \times 95) \times 4.1868] [kJN^{-1}m^{-3}]$ (3)

The LHV of the gas mixture is calculated from final gas composition given by Cheng *et al.* [26]:

$$LHV = (CO\% \times 126.36 + H_2\% \times 107.98 + CH_4\% \times 358.18) \text{ [kJN}^{-1}\text{m}^{-3} \text{]}$$
(4)

where gas components are mentioned in mole percentage.

Gas yield is defined as the flow rate of total inert-free gas produced to flow rate of the dry and ash free value of feedstock [27]. Gas yield, *Y*, is calculated from eq. (5) given by Ngo *et al.* [28].

$$Y = \frac{\text{Volume of gas}}{\text{Mass of sawdust}} \quad [\text{Nm}^3 \text{kg}^{-1}]$$
(5)

The LHV of sawdust is calculated from eq. (6) given by Proll and Hofbauer [29]:

$$LHV_{\text{sawdust}} = (34835 \text{ C} + 93870 \text{ H} - 10800 \text{ O} + 6280 \text{ N} + 10465 \text{ S}) \text{ [kJkg}^{-1} \text{]}$$
(6)

where saw dust elemental components are mentioned in mass fraction.

Cold gas efficiency (CGE) is the ratio of energy present in the syngas to the energy present in the sawdust. Hydrogen production is indicated by CGE [30]. Carbon conversion is defined as the total carbon content of the gas produced (CO, CO₂, and CH₄) to the total carbon content of feedstock [27]. The CGE and carbon conversion efficiency (CCE) are calculated from eqs. (7) and (8) given by Cheng *et al.* [26]:

$$CGE = \frac{LHV_{\text{gas}}}{LHV_{\text{sawdust}}} Y \cdot 100\%$$
⁽⁷⁾

$$CCE = \frac{12Y(\text{CO\%} + \text{CH}_4\% + \text{CO}_2\%)}{22.4C\%} \cdot 100\%$$
(8)

where gas components are mentioned in mole percentage and carbon in mass percentage.

Result and discussion

Biomass gasification influenced by temperature, pressure, fuel composition, moisture content, type of gasifier, gasifying medium and residence time [31, 32]. The analysis of gas composition is done with respect to temperature and equivalence ratio. Oxygen gasification and steam gasification are the common methods followed to improve gas heating value and product gas is free of nitrogen when oxygen and steam are gasifying mediums. For steam, the process becomes allo-thermal, heat has to be supplied externally [33]. Oxygen gasification produces a high yield of hydrogen but the separation of oxygen from air is an energyintensive process [30].

Effect of temperature on gas composition

The operating temperature of the gasifier is limited by the volatile content of the fuel, production of NO_x , ash fusion temperature and material used [34, 35]. Gasification temperature is less than 900 °C for biomass due to the presence of high volatile matter [36]. Temperature affects the gas composition, carbon conversion, amount of char formation, gas yield, gas heating value, and gas efficiencies. Performance of gasifier depends on the thermodynamic behaviour of reactions and balance between endothermic and exothermic reactions [27]. Temperature influences Boudouard reaction, steam reformation and water-gas shift reaction [10]. Gaseous product composition of air and oxygen gasification are comparable but wide

Venugopal, D., et al.: Air and Oxygen Gasification Simulation Analyis of Sawdust THERMAL SCIENCE: Year 2019, Vol. 23, No. 2B, pp. 1043-1053

variation in mole percentage occurs due to the absence of nitrogen in oxygen gasification. The CO formation takes place during the devolatisation stage by carbon partial oxidation, Boudouard reaction and primary water gas reaction [37, 38]. Chemical reactions taking place in the gasifier are listed in tab. 2. Combustible gas composition variation with the operating condition in air and oxygen gasification is shown in fig. 1.

Major gasification reactions	Chemical equations					
Carbon partial oxidation	$C + 1/2 = O_2 \rightarrow CO$					
Carbon oxidation	$C + O_2 \rightarrow CO_2$					
CO oxidation	$\rm CO + 1/2O_2 \rightarrow \rm CO_2$					
Hydrogen oxidation	$H_2 + 1/2O_2 \rightarrow H_2O$					
CH ₄ partial oxidation	$CH_4 + 1/O_2 \rightarrow CO + 2H_2$					
Boudouard reaction	$C + CO_2 \rightarrow 2CO$					
Primary water gas reaction	$C+H_2O \rightarrow CO + H_2$					
Secondary water gas reaction	$C + 2H_2O \rightarrow CO_2 + 2H_2$					
Water gas shift reaction	$\rm CO + H_2O \rightarrow \rm CO_2 + H_2$					
Hydrogasification	$C{+}2H_2 \rightarrow CH_4$					
	$CO + 3H_2 \rightarrow CH_4 + H_2O$					
Mathematican reportions	$\rm CO_2 + 4H_2 \rightarrow 2H_2O$					
Methanation reactions	$2C+2H_2O \rightarrow CH_4+CO_2$					
	$2CO + 2H_2 \rightarrow CH_4 + CO_2$					
Primary steam reforming	$CH_4 + H_2O \rightarrow CO + 3H_2$					
Secondary steam reforming	$CH_4 + 2H_2O \rightarrow CO_2 + 4H_2$					
Dry reforming	$\overline{\mathrm{CH}_4 + \mathrm{CO}_2 ightarrow 2\mathrm{CO} + 2\mathrm{H}_2}$					

 Table 2. Gasification reactions

In air gasification, H₂ increases up to 700 °C for $\phi = 0.3$ -0.45 and for other ϕ values it increases up to 600 °C. In oxygen gasification, H₂ increases up to 800 °C for $\phi = 0.3$ and for other ϕ values it increases up to 700 °C. The decrease of H₂ after peak value is explained by Le Chatelier's principle, above 900 °C hydrogen production decreases due to the exothermic behaviour of water-gas shift reaction [10]. Maximum H₂% of 20.81 and 33.84% are attained at $\phi = 0.3$, in air and oxygen gasification, respectively. The CH₄ content decreases except for initial temperature rise (200-300 °C), the maximum value of 3.99% reached at $\phi = 0.3$ in air gasification. The CH₄ content increases up to 400 °C, the maximum value of 8.49% reached at $\phi = 0.3$ in oxygen gasification. The variation of the CH₄ composition is due to production and consumption of CH₄ in exothermic reactions at low temperature [39]. Rise in temperature decreases CH₄ due to further cracking and reforming reactions [40]. The extended increase of CH₄ in oxygen gasification is explained by the effect of temperature on CH₄ production depends on gasifying agent [11]. Increase in temperature increases CO content for all equivalence ratio, the maximum value of 28.73% and 47.40% are attained at 1200 °C for $\phi = 0.3$ in air and oxygen gasification, respectively. The CO% is less than 4% up to 600 °C, low CO concentration is due to water gas shift reaction. The CO content increases with the rise in temperature due to Boudouard reaction and primary water gas reaction [41-43].



Figure 1. Gas composition of sawdust at different operating conditions for air and oxygen gasification (for color image see journal web site)

Effect of equivalence ratio on gas composition

The optimum value of ϕ for biomass gasification varies from 0.2-0.4 and selection of ϕ values depend on the application of producer gas [44]. In actual practise change in equivalence ratio alters temperature, which in turn changes equilibrium condition and thus gas composition varies [21] but, in simulations equivalence ratio is varied without altering the temperature. The amount of air supplied is 4.35 times greater in mass than oxygen supply for any fuel. Reduction in gasifying medium requirement decreases size and power consumption of auxiliary components of the gasifier. For both air and oxygen mediums, increase in ϕ value decreases H₂ and CH₄ content for all temperature. Up to 400 °C H₂ reduction with the increase in ϕ value is less than 2% for both gasifying mediums. Maximum H₂ reduction of 12.29% and 16.33% are observed in air and oxygen gasification at 1200 °C. After 700 °C CH₄ is less than 1% for both gasification at all ϕ values except for $\phi = 0.3$ and 0.35 in oxygen gasification. Equivalence ratio has no effect on CO up to 500 °C and at higher temperatures, CO% decreases with increase in ϕ value for both gasifying mediums. The CO reduction is justified by combustion occurrence at high ϕ value, improved char burning produces more CO₂ other than combustible gases [45].

Gas heating value and cold gas efficiency

Gasifier bed temperature alters both gas composition and gas heating value. For air gasification, maximum *HHV* of 5.96 MJ/Nm³ is attained at 700 °C for $\phi = 0.3$. At the corresponding operating condition, *LHV* = 5.53 MJ/Nm³ and *CGE* = 82.77% are obtained. For oxygen gasification maximum *HHV* of 9.85 MJ/Nm³ is attained, corresponding *LHV* = 9.18 MJ/Nm³ and *CGE* = 83.95% are obtained at 800 °C for $\phi = 0.3$. Heating value fairly remains constant above 700 °C although the composition varies. Maximum *CCE* of 99.89% reached at 800 °C and remains constant up to 1200 °C for both air and oxygen gasification.

At a high temperature heating value of gas decreases due to the reduction of CH_4 and light hydrocarbon production [45]. Combustion is effective at high temperature which improves CO_2 and N_2 production [46]. Carbon conversion increases with the rise in temperature due to oxidation and gasification reactions which in turn increase the gas yield [27, 35, 47]. Calculated HHV, LHV, CCE, and CGE are shown in fig. 2.



Figure 2. Gas heating value and efficiencies at $\phi = 0.3$ for (a) air and (b) oxygen gasification (for color image see journal web site)

Model validation

Simulation values differ from experimental values due to assumptions present in the equilibrium modelling, in order to accommodate this variation, the accuracy of the simulation has to be analysed. Rice husk air and steam gasification simulation values are compared with experimental values of Karmakar *et al.* [21] and Loha *et al.* [22], respectively. For air gasifi-

cation, simulation temperature range fixed (600-800 °C) and incremented by 25 °C based on experimental operating condition. The equivalence ratios, ϕ , for simulation are 0.25, 0.35, and 0.45. Comparison of experimental and simulation gas compositions are shown in fig. 3 and importance are given to combustible gas components. For $\phi = 0.25$ and 0.35, H₂ values are underpredicted for the selected temperature range. The maximum deviation of 0.52% observed at 725 °C for $\phi = 0.25$ and 1.61% at 750 °C for $\phi = 0.35$, respectively. For $\phi = 0.45$ overprediction of H₂ take place, the maximum deviation of 2.37% occurs at 650 °C. For $\phi = 0.25$ and 0.35 CO value are underpredicted at the initial temperature, a further increase in temperature shows overprediction. Less CO formation in the experiment is due to localised combustion occurrence, favours CO₂ formation. Maximum overprediction deviation of 8.94 and 6.43% occurs at 725 and 700 °C, respectively, CO underprediction deviations are lower than overprediction. For $\phi = 0.45$, maximum overprediction of 7.10% occurs at 650 °C and the further rise in temperature decreases the deviation. For all the operating conditions CH₄ values are underpredicted, more CH4 formation takes place in the experiment due to the non--existence of equilibrium condition. The maximum deviation of 1.98, 2.11, and 1.79% occurs at $\phi = 0.25, 0.35$ and 0.45, respectively, with the corresponding temperature of 700, 700, and 600 °C. The deviations are estimated by RMS values for each operating condition, average RMS value estimated as 3.59. For rice husk steam gasification, temperature varied from 690 °C to 750 °C and steam to biomass ratio 1-1.32. Experimental values of gas composition (H₂, CO, CO₂, and CH₄) are compared with simulation values and average RMS value found to be 4.67, shown in tab. 3.





Figure 3. Rice husk air gasification simulation and experimental results [21]; (a) $\phi = 0.25$, (b) $\phi = 0.35$, (c) $\phi = 0.45$

	S/B ratio	Experimental value [22]				Simulation value				RMS
Temperature [°C]		H2 [%]	CO [%]	CO ₂ [%]	CH4 [%]	H2 [%]	CO [%]	CO ₂ [%]	CH4 [%]	
690	1.32	50.5	14.3	26.6	8.6	56.06	19.06	24.44	0.43	5.59
730	1.32	52.2	16.4	23.5	7.9	55.85	20.81	23.20	0.14	4.82
750	1.00	49.5	23.7	21.2	5.6	53.74	26.49	19.59	0.17	3.80
750	1.32	52.3	17.75	22.25	7.4	55.65	21.59	22.67	0.08	4.46
									AVG	4.67

Table 3. Simulation and experimental result of rice husk steam gasification

Conclusion

Air and oxygen gasification simulation of sawdust is carried out to find out the gas composition at the different operating condition. Gas heating values, cold gas efficiency and carbon conversion efficiency are found. The H₂, CO, CH₄, CO₂, and H₂O are the main gaseous products formed during oxygen gasification, additionally N₂ present in air gasification. All other gaseous products formation is less than 0.5% in both gasifications. Air gasification reaches 99.8% CCE at 600 °C for $\phi = 0.5$ and oxygen gasification reaches it at 700 °C for $\phi = 0.35$. Air gasification reaches, maximum gas HHV of 5.96 MJ/Nm³ at 700 °C for $\phi = 0.3$ and oxygen gasification reaches 9.85 MJ/Nm³ at 800 °C for $\phi = 0.3$. Maximum CGE of 84.37 and 84.73% reached by air and oxygen gasification, respectively, at 1200 °C for $\phi = 0.3$.

Nomenclature

CCE	 – carbon conversion efficiency, [%] 	n_j	 number of moles of component 			
CGE	– cold gas efficiency, [%]	Ν	- number of gas components			
G	- total Gibbs energy, [kJ]	R	– universal gas constant, [kJkmol ⁻¹ K ⁻¹]			
G^0	- Gibbs energy of pure component, [kJ]	RM	S – root mean square			
HHV	- higher heating value of gas mixture, [kJNm ⁻³]	Y	– gas yield, [Nm ³ kg ⁻¹]			
LHV	 lower heating value of 	Cro	ah aumhal			
	gas mixture, [kJNm ⁻³]	0/06	er symbol			
LHV _{sa}	wdust – lower heating value of sawdust, [kJkg ⁻¹]	ϕ	 – equivalence ratio 			

References

- Lumley, N. P. G., et al., Techno-economic Analysis of Wastewater Sludge Gasification: A Decentralized Urban Perspective, *Bioresource Technology*, 161 (2014), Jun., pp. 385-394
- [2] Kim, Y. D., et al., Air-Blown Gasification of Woody Biomass in a Bubbling Fluidized Bed Gasifier, Applied Energy, 112 (2013), Dec., pp. 414-420
- [3] Li, S., Whitty, K. J., Physical Phenomena of Char-Slag Transition in Pulverized Coal Gasification, *Fuel Processing Technology*, 95 (2012), Mar., pp. 127-136
- [4] Bunt, J. R., et al., Behaviour of Selected Major Elements During Fixed-Bed Gasification of South African Bituminous Coal, Journal of Analytical and Applied Pyrolysis, 93 (2012), Jan., pp. 85-94
- [5] Onay, O., Kockar, O. M., Slow, Fast and Flash Pyrolysis of Rapeseed, *Renewable Energy*, 28 (2003), 15, pp. 2417-2433
- [6] Li, S., et al., Fast Pyrolysis of Biomass in Free-Fall Reactor for Hydrogen-Rich Gas, Fuel Processing Technology, 85 (2004), 8-10, pp. 1201-1211
- [7] Senneca, O., Kinetics of Pyrolysis, Combustion and Gasification of Three Biomass Fuels, Fuel Processing Technology, 88 (2007), 1, pp. 87-97
- [8] Silva, L. S., et al., Pyrolysis, Combustion and Gasification Characteristics of Nannochloropsis Gaditana Microalgae, Bioresource Technology, 130 (2013), Feb., pp. 321-331

- [9] Li, C. Z., Importance of Volatile-Char Interactions During the Pyrolysis and Gasification of Low-Rank Fuels-A Review, *Fuel*, *112* (2013), Oct., pp. 609-623
- [10] Senapati, P. K., Behera, S., Experimental Investigation on an Entrained Flow Type Biomass Gasification System using Coconut Coir Dust as Powdery Biomass Feedstock, *Bioresource Technology*, 117 (2012), Aug., pp. 99-106
- [11] Taba, L. E., et al., The Effect of Temperature on Various Parameters in Coal, Biomass and Cogasfication: A review, *Renewable and Sustainable Energy Reviews*, 16 (2012), 8, pp. 5584-5596
- [12] Schuster, G., et al., Biomass Steam Gasification-an Extensive Parametric Modelling Study, Bioresource Technology, 77 (2001), 1, pp. 71-79
- [13] Ismail, T. M., El-Salam, M. A., Parametric Studies on Biomass Gasification Process on Updraft Gasifier High Temperature Air Gasification, *Applied Thermal Engineering*, 112 (2017), Feb., pp. 1460-1473
- [14] Franco, C., et al., The Study of Reactions Influencing the Biomass Steam Gasification Process, Fuel, 82 (2003), 7, pp. 835-842
- [15] Bridgwater, A. V., Renewable Fuels and Chemicals by Thermal Processing of Biomass, *Chemical Engineering Journal*, 91 (2003), 2-3, pp. 87-102
- [16] Shen, L., Simulation of Hydrogen Production from Biomass Gasification in Interconnected Fluidized Beds, *Biomass and Bioenergy*, 32 (2008), 2, pp. 120-127
- [17] Shayan, E., et al., Hydrogen Production from Biomass Gasification; A Theoretical Comparison of Using Different Gasification Agents, Energy Conversion and management, 159 (2018), Mar., pp. 30-41
- [18] Shweta, S., Pratik, N. S., Air-Steam Biomass Gasification; Experiments, Modeling and Simulation, Energy Conversion and management, 110 (2016), Feb., pp. 307-318
- [19] Karl, M. B., et al., Steam/Oxygen Gasification System for the Production of Clean Syngas from Switchgrass, Fuel, 140 (2015), Jan., pp. 282-292
- [20] Niu, M., et al., Oxygen Gasification of Municipal Solid Waste in a Fixed Bed Gasifier, Chinese Journal of Chemical Engineering, 22 (2014), 9, pp. 1021-1026
- [21] Karmakar, M. K., et al., Investigation of Fuel Gas Generation in a Pilot Scale Fluidized Bed Autothermal Gasifier Using Rice Husk, Fuel, 111 (2013), Sep., pp. 584-591
- [22] Loha, C., et al., Performance of Fluidized Bed Steam Gasification of Biomass-Modeling and Experiment, Energy Conversion and Management, 52 (2011), 3, pp. 1583-1588
- [23] Behainne, J. J. R., Martinez, J. D., Performance Analysis of an Air-Blown Pilot Fluidized Bed Gasifier for Rice Husk, *Energy for Sustainable Development*, 18 (2014), Feb., pp. 75-82
- [24] Lahijani, P., Zainal, Z. A., Gasification of Palm Empty Fruit Bunch in a Bubbling Fluidized Bed: A Performance and Agglomeration Study, *Bioresource Technology*, 102 (2011), 2, pp. 2068-2076
- [25] Xiao, R., et al., High temperature Air/Steam Blown Gasification of Coal in a Pressurized Spout-Fluid Bed, Energy Fuels, 20 (2006), 2, pp. 715-720
- [26] Cheng, G., et al., Gasification of Biomass Micron Fuel with Oxygen-Enriched Air: Thermogravimetric Analysis and Gasification in a Cyclone Furnace, Energy, 43 (2012), 1, pp. 329-333
- [27] Fermoso, J., et al., High-Pressure Co-Gasification of Coal with Biomass and Petroleum Coke, Fuel Processing Technology, 90 (2009), 7-8, pp. 926-932
- [28] Ngo, S. I., *et al.*, Performance Evaluation for Dual Circulating Fluidized-Bed Steam Gasifier of Biomass Using Quasi-Equilibrium Three-Stage Gasification Model, *Applied Energy*, 88 (2011), 12, pp. 5208-5220
- [29] Proll, T., Hofbauer, H., H2 Rich Syngas by Selective CO2 Removal from Biomass Gasification in a Dual Fluidized Bed System-Process Modelling Approach, *Fuel Processing Technology*, 89 (2008), 11, pp. 1207-1217
- [30] Bhattacharya, A., et al., Exergy Based Performance Analysis of Hydrogen Production from Rice Straw Using Oxygen Blown Gasification, Energy, 69 (2014), May, pp. 525-533
- [31] Ahmed, T. Y., et al., Mathematical and Computational Approaches for Design of Biomass Gasification for Hydrogen production: A Review, *Renewable and Sustainable Energy Reviews*, 16 (2012), 4, pp. 2304-2315
- [32] Mohammed, M. A. A., et al., Air Gasification of Empty Fruit Bunch for Hydrogen-Rich Gas Production in a Fluidized-Bed Reactor, Energy Conversion and Management, 52 (2011), 2, pp. 1555-1561
- [33] Kern. S., et al., Gasification of Lignite in a Dual Fluidized Bed Gasifier-Influence of Bed Material Particle Size and the Amount of Steam, Fuel Processing Technology, 111 (2013), July, pp. 1-13
- [34] Seo, M. W., et al., Gasification Characteristics of Coal/Biomass Blend in a Dual Circulating Fluidized Bed Reactor, Energy Fuel, 24 (2010), 5, pp. 3108-3118

- [35] Pinto, F., et al., Effect of Experimental Conditions on Co-Gasification of Coal, Biomass and Plastics Wastes with Air/Steam Mixtures in a Fluidized Bed System, Fuel, 82 (2003), 15-17, pp. 1967-1976
- [36] Mondal, P., et al., Syngas Production through Gasification and Cleanup for Downstream Applications-Recent Developments, Fuel Processing Technology, 92 (2011), 8, pp. 1395-1410
- [37] Sun, S., et al., Experimental Research on Air Staged Cyclone Gasification of Rice Husk, Fuel Processing Technology, 90 (2009), 4, pp. 465-471
- [38] Wang, F. Y., Bhatia, S. K., A Generalised Dynamic Model for Char Particle Gasification with Structure Evolution and Peripheral Fragmentation, *Chemical Engineering Science*, 56 (2001), 12, pp. 3683-3697
- [39] Pohorely, M., et al., Gasification of Coal and PET in Fluidized Bed Reactor, Fuel, 85 (2006), 17-18, pp. 2458-2468
- [40] Gil, J., et al., Biomass Gasification with Air in a Fluidized Bed: Effect of the In-Bed Use of Dolomite under Different Operation Conditions, *Industrial and Engineering Chemistry Research*, 38 (1999), 11, pp. 4226-4235
- [41] Asadullah, M., et al., A Comparison of Rh/CeO₂/SiO₂ Catalysts with Steam Reforming Catalysts, Dolomite and Inert Materials as Bed Materials in Low Throughput Fluidized Bed Gasification Systems, Biomass and Bioenergy, 26 (2004), 3, pp. 269-279
- [42] Lapuerta, M., et al., Gasification and Co-Gasification of Biomass Wastes: Effect of the Biomass Origin and the Gasifier Operating Conditions, Fuel Processing Technology, 89 (2008), 9, pp. 828-837
- [43] Hernandez, J. J., et al., Gasification of Grapevine Pruning Waste in an Entrained-Flow Reactor: Gas Products, Energy Efficiency and Gas Conditioning Alternatives, Global NEST Journal, 12 (2010), 2, pp. 215-227
- [44] Narvez, I., et al., Biomass Gasification with Air in an Atmospheric Bubbling Fluidized Bed. Effect of Six Operational Variables on the Quality of the Produced Raw Gas, Industrial and Engineering Chemistry Research, 35 (1996), 7, pp. 2110-2120
- [45] Mansaray, K. G., et al., Air Gasification of Rice Husk in a Dual Distributor Type Fluidized Bed Gasifier, Biomass and Bioenergy, 17 (1999), 4, pp. 315-332
- [46] Wu, C. Z., et al. Operational Characteristics of a 1.2-MW Biomass Gasification and Power Generation Plant, Biotechnology Advances, 27 (2009), 5, pp. 588-592
- [47] Chaiprasert, P., Vitidsant, T., Promotion of Coconut Shell Gasification by steam Reforming on Nickel-Dolomite, American Journal of Applied Sciences, 6 (2009), 2, pp. 332-336