# STUDY ON THERMODYNAMIC FUNCTIONS OF TRADITIONAL BUILDING WINDOWS BASED ON CHARACTERS

# by

# Yuelian HU<sup>\*</sup> and Jing ZHUO

### Wenzhou Ploytechnic, Wenzhou, China

Original scientific paper https://doi.org/10.2298/TSCI200522251H

The indoor light environment of the building has an extremely important influence on its own use function, and there are many factors that affect the indoor light environment of the building, such as the surrounding environment of the building, the interior decoration of the building, and the design of the window. The window is used as the building envelope. An important part of the structure is responsible for lighting and ventilation meet the requirements of the indoor environment. It exists as a lighting device for the building. The lighting performance of the windows not only meets people's requirements for living comfort, but also consumes energy in the building. It will have a very important impact. A variety of window shapes start from different functional needs. The comprehensive use of these window shapes by traditional buildings together creates its unique thermodynamic function. This article analyzes cold regions based on the analysis method of thermodynamic functions. Solar heat gain from traditional building windows.

Key words: windows, light environment, daylight, thermodynamic function

# Introduction

With the rapid development of China's economy, the contradiction between insufficient energy resources and the deterioration of the ecological environment has become increasingly apparent. Protecting the environment and conserving resources have become a hot topic of discussion [1]. Windows are an indispensable and important part of residential buildings, and they are also buildings. The weakest part of the thermal insulation performance of the outer envelope structure. Therefore, it is undoubtedly an active and effective attempt to use the windows as a breakthrough point in building energy saving and to combine the actual geographical environment of the building with the energy saving design of the building [2]. Traditional Chinese architecture in the window, there are various shapes, including long windows installed between the upper and lower sills, and small windows used for ventilation on the upper part of the wall [3]. For general multi-storey residential buildings, traditional lighting The method is based on natural lighting. Usually, in order to meet the indoor lighting requirements, a certain area of windows is opened on the exterior wall of the building [4] A variety of window shapes start from different functional requirements. The comprehensive use of the window shape has jointly created its unique thermodynamic function. The window is the main channel for daylighting. The larger the window area, the more light is obtained [5]. In other words, the greater the volume ratio of the window building, the greater the value, the rapid expansion of the current building scale, out of consideration for the building energy efficiency, make full use of natural light, to provide a good indoor environment for building construction, can save a lot of energy [6].

<sup>\*</sup> Corresponding author, e-mail: zj13777772680@163.com

Natural light, as a natural light source that people are accustomed to, can also maximize the comfort of building interiors and create a good working and living environment [7]. In view of the characteristics of heat, humidity, rain and strong radiation, traditional buildings in some parts of China have proposed specific measures to adapt to the local climate and environment and meet green energy-saving requirements [8]. Natural light has become a clean light source due to its reproducibility and pollution-free. A large amount of natural light has a positive effect on protecting the ecosystem and conserving energy by reducing pollution while conserving resources [9]. In winter, in severe cold areas and cold areas, a large amount of indoor heat is lost due to cold wind penetration and heat conduction and radiation in windows. In buildings In daylighting design, knowing the two main elements of the building's main use and function and the window-to-ground area ratio, it is possible to calculate the accurate daylighting coefficient [10]. There are many factors affecting the natural daylighting of the building. To provide the best indoor environment for personnel, it is necessary for the architect to make full use of natural lighting through the size design of the window [11]. The building's structure and windows are designed so that the interior of the building is well lit by natural light. Natural lighting can be fully utilized to save energy and protect the environment.

Natural light is a light source that people are accustomed to. Human eyes have higher sensitivity under natural light than under artificial light [12]. In addition, natural light comes from the Sun, which is a huge and safe clean light source. Cold regions in our country have the characteristics of low winter temperature, long duration, short time when the Sun shines indoors during the day, low outdoor temperature at night, and a lot of heat energy lost through windows [13]. The design and application of energy-saving windows that can meet the multi-functional requirements of lighting, ventilation, landscape, etc. will be the inevitable direction of the future development of windows [14]. Energy conservation is an important part of a resource-saving society. Building energy consumption accounts for a large proportion of the total energy consumption and is the energy-using field with the greatest energy-saving potential. Therefore, it should become the top priority of energy conservation work [15]. Reducing the heat energy consumption of windows is of great significance to the energy-saving effect of buildings. With the further improvement of China's building energy efficiency standards, the energy-saving design of windows will become more and more important [16]. As an important part of building envelope, windows take on lighting and ventilation meet the requirements of indoor environment [17]. How to do a good job in the huge and arduous task of building energy conservation on the premise of ensuring economic development and environmental protection is a serious challenge we will face [18]. Based on the method of thermodynamic function analysis, this paper analyzes the solar heat gain of traditional building windows in cold regions.

### Parameter selection and model establishment

The main purpose of building design is to provide a healthy, comfortable, and efficient working and living environment for people. Under the background of today's energy crisis, building energy conservation is also booming. The exterior doors and windows of buildings are important components of the building's exterior protection structure. In addition the most basic enclosure functions, they also have the functions of heat preservation, lighting and ventilation. In order to increase revenue and reduce expenditure, people have turned their attention clean energy sources such as solar energy. Natural lighting and related technologies are particularly important. In order to study the influence of exterior windows on building energy consumption and lighting environment, we must first understand the influence principle and evaluation method of exterior windows on building indoor thermal environment and lighting environment,

902

Tabla	1	Minimum	indoor	lighting	standarde
Table	1.	1VIIIIIIIIIIIIII	muoor	ngnung	stanuarus

Poom name	Side lighting		
Koom name	Use the lowest coefficient [%]	Window to floor area ratio	
Bedroom, living room, kitchen	1	1:7	
Staircase	0.5	1:12	

Table 2. Minimum window area of each room

Room name	Bedroom 1	Bedroom 2	Bedroom 3	Living room	Study	Kitchen
Floor area [m <sup>2</sup> ]	15.46	11.17	8.48	30.95	7.42	15.89
Hole area [m <sup>2</sup> ]	2.36	1.61	1.18	4.55	1.1	2.29
Width $\times$ height [m <sup>2</sup> ]	1.6×1.3	1.2×1.3	0.8×1.3	2.9×1.5	0.8×1.3	1.5×1.3

and then select appropriate software as analysis and research tools [19]. Because the hot summer and cold winter zone in China spans a large area, the climatic conditions may vary greatly between different cities in the hot summer and cold winter zone. The quantity of daylighting only meets people's visual function requirements for the light environment when they are indoors, while the quality of daylighting is the basic requirements for the safety, comfort and health of the light environment. As the name implies, the ratio of window area to floor area is the ratio of window opening area to floor area. Under specific lighting conditions, architects can make a preliminary estimation of the lighting coefficient of architectural design by comparing the area of windows and floors with different lighting forms. If you want to under-



stand the indoor light environment and thermal environment of the building, it is necessary to analyze the factors that affect the intensity of solar radiation and the movement law of the Sun's position.

According to the *Residential Design Code*, the minimum daylighting standard for ordinary residential buildings is shown in tab. 1. According to this specification, the ratio of window area to floor area is 1:7, and the window area under the condition of minimum lighting can be calculated from the specific size of each room in the residential unit type. The specific calculation results are shown in tab. 2. By comparing the data in tab. 2 with the actual window size of the hole shown in fig. 1, it can be found that the window openings on each wall surface in this example are larger than the minimum lighting area specified in the specification.

In order to ensure the use efficiency of construction engineering materials and reduce the cost of construction, project management personnel must strengthen the management and strict control of materials and their use at the construction site. Use the existing technology to establish a multi-mode collaborative working environment with integrated integration Collaborative work support platform of the multimedia mode. The co-operative design operation process is shown in fig. 2.



Figure 2. Co-operative design and operation process of office building engineering

Difference sequence:

In the window structure, not only the heat loss caused by the temperature difference between the two sides of the air, but also the heat caused by the solar radiation and the heat loss caused by the radiation the sky. The heat storage and heat release of the envelope structure, radiant heat exchange on all surfaces of the room, indoor equipment, lighting, and personnel are all constantly changing. In the traditional design method, the construction specialty and equipment specialty are disconnected, and the equipment engineer need to use energy analysis software for energy analysis after entering building data.

Extraction and conversion based on specific information format in the building information model, to achieve the docking and sharing of different professional software data. Dimensionless processing of the comparison sequence and the reference sequence. In this paper, the mean method is used to process:

$$E_{cr} = \frac{c_p}{E} \int_0^t \sigma^2 \mathrm{d}t \tag{1}$$

(2)

 $W_{0i} = \frac{1}{n} \sum_{i=1}^{n} r_{0i}$ 

$$F_{Adh} = F - \frac{4}{3} E^r \sqrt{R(d - d_0)^3}$$
(3)

For a healthy indoor light environment, in order to avoid the glare caused by strong brightness contrast in human vision, some commonly used principles should also be adhered to. The important source of heat on the earth is solar radiant energy, which has different effects on the earth. The regional climate has an extremely important role and is the main factor that determines the climatic conditions. All buildings on the earth are directly or indirectly affected by solar radiation. The factors that affect the indoor thermal environment of office buildings are divided into internal disturbance and external disturbance are two types. External disturbance mainly refers to climatic parameters such as air temperature and humidity, solar radiation, etc. [20]. Internal disturbance is mainly indoor indoor heat sources such as equipment, lighting and personnel. Compared to other latitudes, the average temperature in July in China is hotter in summer and colder in winter than other regions of the same latitude, but the average temperature in January is 5-10 °C cooler than the same latitude in the world, which is the lowest winter temperature in the same latitude in the world [21]. If we can determine the position of the Sun at different seasonal times, we can determine the building distance, building orientation and daylight hours. In addition, we need to make design calculations for the air conditioning load and the natural daylighting of the building.

# Thermodynamic function analysis of traditional building windows

# Determination of thermal parameters of windows

The forms of heat gain and heat loss of residential windows include: solar heat gain, heat exchange, and air penetration, and each of these forms has corresponding evaluation parameters, namely the solar heat gain coefficient, the entire window heat transfer coefficient, and air permeability. The larger the value of the daylighting coefficient, the larger the window area is, the more beneficial it is. Due to the health and psychological reasons of the residents in the northern hemisphere, they hope to get enough sunlight, especially for ordinary residential windows, it is best to face the sun or south. With the development of economy and the continuous advancement of technology, its development and evolution can be described with each passing day. Since the industrial revolution, the development of technology has changed the world. The amount of solar energy through the window includes two parts: one is the heat that enters the room directly through the window, and the other is after each layer of glass absorbs the amount of solar energy, it acts as an independent small heat source and indirectly radiates heat to the room.

The direct sunlight energy gradually accumulates, so that the indoor air temperature increases continuously, and is proportional to the solar energy transmission ratio of the window and the area of the window, which will definitely increase the air conditioning load in summer [22]. In winter, regardless of the south-facing window or north-facing the heat dissipation of windows and large-area windows must increase the heating load. Thus, the area of the lighting window is not as large as possible [23]. The structure of the window will develop in the direction of energy saving in the future, that is, a large number of double-layer insulating glass and three-layer hollow glass, coated insulating glass, *etc.*, to ensure certain energy saving requirements for heat preservation or insulation. Table 3 shows the standard value of the lighting coefficient on the reference plane of each lighting level.

	Side li	ghting	Daylighting		
Lighting level	Standard value of daylighting coefficient [%]	Standard value of indoor natural light [lx]	Standard value of daylighting coefficient [%]	Standard value of indoor natural light [lx]	
Ι	5	780	5	750	
II	4	580	2	420	
III	3	460	3	320	
IV	2	310	1	160	
V	1	160	0.6	80	

Table 3. Standard values of daylighting coefficients	
on the reference plane of each daylighting level	

Building energy conservation based on building information modelling (BIM) technology can solve the problem of data conversion in the process of building design and energy conservation design and improve work efficiency. Using BIM technology, data can be input into the model, thus establishing a virtual model. Figure 3 is an optimization model of BIM construction engineering.

The choice of parameters in the BIM system is critical to whether the algorithm converges. According to the initial conditions of BIM, for the convenience of analysis, only the discrete time is considered. It can be concluded that:



Figure 3. The BIM building engineering optimization model



Figure 4. Comparison of algorithm performance before and after storage optimization



The iteration termination condition is generally selected as the maximum number of iterations or the optimal position searched by the particle swarm so far meets a predetermined minimum adaptation threshold. The position and velocity of each particle are changed according to the following formula:

$$\tau_b = \frac{\rho g n^2 Q^2}{A^2 R^{1/3}} \tag{5}$$

The size of the window area can directly affect the indoor environmental quality of the building, such as thermal insulation, heat insulation, and sound insulation, and ultimately affect the quality of life of people indoors. Architectural modelling considers the physical properties of objects when modelling. Fractal technology and particle systems. It is a typical physical modelling method. Fractal technology can describe data sets with self-similar characteristics. Figure 4 shows the comparison of algorithm performance before and after storage optimization.

When the building is in the stage of energy-saving design, the application effect of sin-

gle energy-saving technology in the building cannot be simply analyzed. The comprehensive impact of various energy-saving technologies on building energy consumption and the impact level of energy consumption of various energy-saving technologies should be analyzed in detail. The structural design of building skin is optimized by combining high strength load-bearing materials with light thermal insulation materials with low thermal conductivity. Due to the combined effect of solar radiation and temperature difference between indoor and outdoor, heat is transferred into the room through the window glass. After sunlight hits the surface of the window glass, part of it is reflected off and will not become the heat of the room. As the part that is closest to the outdoor environment, it is the key to calculate the building energy consumption correctly calculate the unstable heat transfer of the wall thermal system under any disturbance. Geometrical modelling is the first development in the information design of window thermodynamic lay-out. Geometrical modelling deals with basic problems such as geometry and shape representation of objects, research on graphic data structure, *etc*. The path density, node number and center potential are analyzed. As shown in tab. 4.

Tabla 4. Structural analysis of building lay-out information design

The internet	Path density	Number of nodes	Central potential	
Encounter information	1411	2133	0.752	
Interactive information	2024	2083	0.563	
Weighted sum	613	2622	0.662	

To determine the conditions under which exclusion and attraction operations are performed, we will introduce a diversity control method:

$$I_i = \left[\sum_{j=1}^p \omega_j^m y_{ij}^m\right]^{1/m} \tag{6}$$

The iteration termination condition is generally selected as the maximum number of iterations or the optimal position searched by the particle swarm so far meets a predetermined minimum adaptation threshold. The position and velocity of each particle are changed according to the following formula:

$$\theta(P) = Ln\left(\frac{P}{1-P}\right) = \alpha + \sum \beta_i X_i + \xi \tag{7}$$

The choice of parameters in the window thermodynamic lay-out system is crucial to the algorithm's convergence. According to the initial conditions of the building lay-out, for the convenience of analysis, only discrete time is considered. It can be concluded:

....

$$K_{s,d} = \frac{1}{MN} \sum_{m=1}^{M} \sum_{n=1}^{N} \frac{\left\| W_{s,d}(m,n) \right\| - \mu_{s,d}}{\sigma_{s,d}^{4}}$$
(8)

In the case of solar radiation, ignoring the heat transfer of the window frame and the heat transfer of the glass edge and the window frame, it can be considered that the window in this example consists of only two layers of glass and a space between the layers. The actual building and system are auxiliary, Uncertain and non-linear, so we have to use assumptions, simplifications and approximations in the modelling process to get the calculation results. The theoretical value of the solar heat gain coefficient is 0 to 1, and the actual value is about 0.15 to 0.80. Under the same conditions, the smaller the value is, the less heat is generated by the solar radiation through the window. The development trend of the constituent materials of the window will be to choose eco-friendly energy-saving frame materials and connect the frame materials to the high performance glass system through connecting members. Make windows have good air tightness [24]. Due to the introduction of new technology development and the actual need to save energy, the development of windows in the future will inevitably further develop from the development of its functions, composition materials, and construction [25]. The higher the accuracy of the requirements, the higher the requirements for the simulation, and the greater the workload of the simulation. Therefore, when modelling, you need to consider the trade-off between the two.

### Calculation of heat transfer of windows

The heat transfer methods of windows include: radiant heat transfer with indoor and outdoor environments, convective heat transfer between the inner and outer surface, radiant heat transfer and convective heat transfer between glass layers, heat transfer in the glass layer, and absorption of solar radiation heat by the glass. Part of the light directly enters the room through the windows, and part of the heat is transferred to the room by the absorption of solar radiation energy by the various layers of glass. The meaning of daylight is also constantly changing and rich, and the only way to open the window is also changing. The daylighting is to let the light enter the room through the window, which is a kind of passive lighting. Solar radiation encounters the scattering of gas molecules and dust in the atmosphere, and the radiant energy reaching the surface of the earth in a diffuse form is called scattered solar radiation. The relative value is the daylighting coefficient. It is the illuminance generated by the diffusely reflected light from a certain point on a given horizontal plane in the room under the illumination of the diffuse cloudy sky. The ratio of the illuminance caused by the diffuse reflection of the sky on the horizontal plane. The use of modern lighting materials, such as glass curtain walls, prism glass, special coated glass, *etc.* Good lighting quality plays a role.

The window thermodynamic model based on the information design task can be used to solve the possible design problems and quality problems of the project in advance through collision detection and other forms. The optimization performance parameters of residential lay-out before and after optimization are shown in tab. 5.

 Table 5. Performance parameters of optimized topology for residential lay-out before and after optimization

	Before optimization	After optimization
Rows	31	46
Number of columns	21	31
Monitoring points	651	1426

The survey results for the transmission and distribution system show that the pumps in the sample buildings basically did not use the control strategy of frequency conversion adjustment. The various types of equipment were not cleaned and organized in time during the operation. There are certain energy-saving technical measures for the building envelope protection The energy-saving potential of existing buildings should continue to promote the energy-saving reconstruction of the outer envelope of existing buildings. Buildings are closely related to the environment in which they are located, and each base has its own unique characteristics. Although high rise buildings have certain ventilation advantages, they are often subject to The direct and diffuse intensity of the sun is also higher.

In order to determine under what circumstances the repulsive operation and the attracting operation are executed, we will introduce a diversity control method:

$$F_{ij}^{t} = \frac{1}{N_c} \sum_{c \in N_c} \frac{f^{t} t_i n_j}{1 + a_{kl}^{c} n_k n_l}$$
(9)

The training and learning process of the window thermodynamic model is a process in which the error value between the network output value and the expected value gradually decreases until the error meets the requirements. Define the error:

$$\sigma_{ij} = \frac{1}{V} \sum_{c \in N_c} f_i^c d_j^c \tag{10}$$

It is applied to window thermodynamic lay-out optimization. The following formula:

$$C_n^P = \frac{\sum N_s^P n_c^P}{N_s^P} \tag{11}$$

The particle speed is updated during the run:

$$\Delta M = \left[\frac{\sum n_i \left(\Delta M_i\right)^m}{\sum n_i}\right]^{1/m} \tag{12}$$

The outdoor illuminance of a building often changes, which inevitably causes the indoor illuminance to change accordingly. It cannot be a fixed value, therefore, the requirements for the amount of daylighting use relative values. Scattered radiation is non-directional, and it only accounts for total radiation. A small part of the energy, and the direct solar radiation, because of its large proportion, is the main factor affecting the total solar radiation. After the solar radiation passes through the atmosphere, its intensity and spectral energy distribution both change to some extent. At present, the main types of daylighting are side lighting, top lighting and both mixed lighting, with the increasing density of urban buildings, more and more high rise buildings, the mutual shading is more serious, directly affecting the amount of light. In the design of buildings, sometimes use the inner wall lighting methods such as the patio lighting well or the reflector device can supplement the insufficient lighting of the outer wall, and also avoid the direct sunlight and dazzling spots of the Sun. Human beings have been adapted to long-term life under the Sun, both psychologically and physiologically. In order to obtain all kinds of information, and to seek environmental sanitation and physical health, light has become a necessity and tool for people's lives. Currently, daylight still means establishing a natural light environment, and as technology advances, the meaning of daylight continues to expand. One day, daylighting will not only be used to create natural and artificial light environments, but also to provide cheap, clean energy for other purposes.

### Conclusion

The thermal design of the windows of residential buildings has always been a difficult point in energy-saving design. Opening windows of houses in severe cold areas cannot blindly increase the area. Energy-saving design must be carried out in accordance with local climatic conditions and local conditions. There are many factors that affect the natural lighting of the building interior. This article discusses the effect of window-to-wall ratio, window sill height, and window shape on the natural lighting of the building. The thermal design of the window part of a residential building has always been a difficult point in energy-saving design. Through the analysis of this case, we can conclude that the opening of windows does not blindly increase the area, and energy-saving design must be carried out in accordance with local climatic conditions according to local conditions. For areas where the latitude is not very high, solar energy is abundant, and the average outdoor temperature in winter is not very low, it is recommended to increase the area of south-facing windows use as much solar energy as possible to save energy. In the vicinity of the window, the position of the window should not be too high. Although the window is too high to facilitate the lighting in deep and large places, it can affect the overall average lighting performance of the building and people's visual comfort. In addition to the windows themselves. There are also many factors that affect the natural daylighting of a building's interior, such as the screening of the building surroundings, the decoration of the building's interior, the design of the building's exterior shading, and the installation of lighting auxiliary components.

### References

- Xiong, Z. J, aMai, H., Analysis on the Thermodynamic Function of Windows in Traditional Buildings in Lingnan Area, *Shanxi Architecture*, 10 (2015), 41, pp. 194-196
- Mao, Y. L., Evaluation of the Thermodynamic Time Constant of Buildings, *Business Management*, 17 (2019), 1, pp. 345-345
- [3] He, Y., et al., Strategies for Improving the Lighting Quality of Public Building Spaces: Application Research on Advanced Lighting Window Systems and Materials, New Construction, 4 (2019), 4, pp. 75-79
- [4] Xu, J., Effects of Different Shading forms of South-Facing Windows on Indoor Lighting in Xi'an, Energy Efficiency in Buildings, 6 (2016), 44, pp. 61-64
- [5] Li, Z. L., and Qin, C. C., Significant analysis of factors affecting building daylighting based on orthogonal experiment. Architecture Technology, 46 (2015) 11, pp. 1002-1005
- [6] Boscarino, G., Moallem, M., Daylighting Control and Simulation for LED-Based Energy-Efficient Lighting Systems. *IEEE Transactions on Industrial Informatics*, 12 (2016), 1, pp. 301-309

- [7] Lavin, C., Fiorito, F., Optimization of an External Perforated Screen for Improved Daylighting and Thermal Performance of an Office Space, *Procedia Engineering*, 180 (2017), May, pp. 571-581
- [8] Flourentzou, F., et al., Design and Performance of Controlled Natural Ventilation in School Gymnasiums, International Journal of Ventilation, 16 (2016), 2, pp. 1-12
- [9] Pham, K., et al., Appraisal of the Visual Environment in an Industrial Factory: a Case Study in Subtropical Climates, Journal of Daylighting, 3 (2016), 2, pp. 12-26
- [10] Lucia, D. V., et al., Indoor Daylight Simulation Performed on Automatically Generated as-Built 3-D Models, Energy and Buildings, 68 (2014), 1, pp. 54-62
- [11] Theodorson, J., Energy, Daylighting, and a Role for Interiors, *Journal of Interior Design*, 39 (2014), 2, pp. 37-56
- [12] Voll, S., A Method of Optimizing Fenestration Design for Daylighting to Reduce Heating and cooling loads in offices, *Journal of Civil Engineering and Management*, 20 (2014), 5, pp. 714-723
- [13] Feng, W. G., The Important Role of Architectural Glass in Energy-Saving Plastic Doors and Windows, Doors and Windows, 4 (2014), pp. 34-38
- [14] Guan, J. J., et al., The Role of Natural Lighting in Shaping the Atmosphere of Buildings, Huazhong Architecture, 10 (2014), pp. 51-55
- [15] Manzan, M., Padovan, R., Multi-Criteria Energy and Daylighting Optimization for an Office with Fixed and Moveable Shading Devices, *Advances in Building Energy Research*, 9 (2015), 2, pp. 238-252
- [16] Roshan, M., Barau, A. S., Assessing Anidolic Daylighting System for Efficient Daylight in Open Plan Office in the Tropics, *Journal of Building Engineering*, 8 (2016), Dec., pp. 58-69
- [17] Kousalyadevi, G., Lavanya, G., Optimal Investigation of Daylighting and Energy Efficiency in Industrial Building Using Energy-Efficient Velux Daylighting Simulation, *Journal of Asian Architecture and Building Engineering*, 18 (2019), 4, pp. 271-284
- [18] Masiokas, S. V. P., The Influence of Room's Daylighting on the Contrast of Diffuse Screen Image, Finante-Provocarile Viitorului (Finance-Challenges of the Future), 52 (2015), 9, pp. 9-10
- [19] Pitts, J. F., A New Methodology for Successful Daylighting Design, Architectural Record, 203 (2015), 11, pp. 234-235
- [20] Ladislav, K., Kocifaj. M., Statistical Cloud Coverage as Determined from Sunshine Duration: A Model Applicable in Daylighting and Solar Energy Forecasting, *Journal of Atmospheric and Solar-Terrestrial Physics*, 150-151 (2016), Dec., pp. 1-8
- [21] Cui, S., et al., A Global Modelling Approach of Natural Ventilation with Acoustic and Daylighting Constraints, International Journal of Ventilation, 15 (2016), 3-4, pp. 233-252
- [22] Nezamdoost, A., Wymelenberg, K. V. D., A Daylighting Field Study Using Human Feedback and Simulations to Test and Improve Recently Adopted Annual Daylight Performance Metrics, *Journal of Building Performance Simulation*, 10 (2017), 1, pp. 1-13
- [23] Matthews, J. et al., Real Time Progress Management: Re-Engineering Processes for Cloud-Based BIM in Construction, Automation in Construction, 58 (2015), Oct., pp. 38-47
- [24] Johansson, M. et al., Real-Time Visualization of Building Information Models (BIM), Automation in Construction, 54 (2015), June, pp. 69-82
- [25] Song, S., et al., Development of a BIM-Based Structural Framework Optimization and Simulation System for Building Construction, Computers in Industry, 63 (2012), 9, pp. 895-912

Paper submitted: May 22, 2020 Paper revised: June 30, 2020 Paper accepted: July 7, 2020 © 2021 Society of Thermal Engineers of Serbia Published by the Vinča Institute of Nuclear Sciences, Belgrade, Serbia. This is an open access article distributed under the CC BY-NC-ND 4.0 terms and conditions

910