# AN ITERATIVE APPROACH TO VISCOELASTIC BOUNDARY-LAYER FLOWS WITH HEAT SOURCE/SINK AND THERMAL RADIATION

#### by

## Syeda A. IQBAL<sup>a</sup>, Muhammad SAJID<sup>b</sup>, Khalid MAHMOOD<sup>b</sup>, Muhammad NAVEED<sup>c\*</sup>, and Muhammad Yaqub KHAN<sup>a</sup>

<sup>a</sup> Department of Basic Sciences, Riphah International University, Islamabad, Pakistan <sup>b</sup> Department of Mathematics and Statistics, International Islamic University, Islamabad, Pakistan <sup>c</sup> Department of Mathematics,

Khwaja Fareed University of Engineering and Information Technology, Rahim Yar Khan, Pakistan

Original scientific paper https://doi.org/10.2298/TSCI1802020031

In this study effect of radiation on the viscoelastic Walter-B fluid is investigated with heat sink/source. Sakiadis, Blasius, and stagnation point flows are considered at constant surface temperature. Some suitable similarity variables have been utilized to transform governing equations into ODE. An iterative approach based on the Legendre wavelet spectral collocation method is applied for the solution of the resulting equations. The obtained results are validated by plotting the residual error curves in each case. Temperature and heat transfer rate at wall are analyzed to investigate the influence of involved parameters. It is found that the Legendre wavelet spectral collocation method is very efficient and can be employed for the solutions of various non-Newtonian flow problems.

Key words: boundary-layer flow, heat transfer, radiation effects, wavelets, collocation method, shooting method

## Introduction

The boundary-layer phenomenon in non-Newtonian fluids is of great interest for the recent researchers due to its applications in the industry and applied sciences. The boundary-layer flow on the flat plate was studied by [1-6]. Sakiadis [2, 3] was the first who studied the flow on a moving plate by applying boundary-layer assumptions to the 2-D flow. The same problem by assuming a stretching velocity at the surface was first analyzed by Crane [4]. Heat transfer analysis for the boundary-layer flow due to continuously moving plate was investigated by Tsou *et al.* [7]. Takar *et al.* [8] discussed the impact of fluid properties for the boundary-layer flow of a viscous fluid due to a moving surface. Hiemenz [9] considered the boundary-layer approximation study the flow towards a stagnation point. Motivated by these pioneering works the 2-D flows utilizing the boundary-layer approximations have been investigated extensively in the literature [10-22] and references therein.

The influence of heat transfer along with thermal radiation effects on the flows inside boundary-layer in different situations have been investigated by several researchers [23-28]. In studies [23, 24] Cortell investigated the effects of radiations on the Sakiadis and Blasius flows for different emerging parameters. Impact of thermal radiation on the flow due to boundary-layer over an exponentially stretching surface is examined by Sajid and Hayat [29]. These studies

<sup>\*</sup>Corresponding author, e-mail: rana.m.naveed@gmail.com

are important in solar power technology, electrical power generation, cooling of electronic tools and nuclear reactors, satellites, space and other industrial areas.

Viscoelastic fluids have importance in industry, biological fluids, geophysics, *etc.* Due to this fact in recent years, the study of viscoelastic fluids gains considerable attention of researchers working in this area. Some important investigations reflecting the viscoelastic effects are presented by [30-36]. Heat transfer in viscoelastic fluids due to boundary-layer in the presence of thermal radiations and constant suction is discussed by [37-39].

The present investigation is devoted to investigate radiation and heat source/sink effects for Blasius, Sakiadis, and stagnation point flows of Walter-B fluid [40]. The velocity profile overshoot in these flows have already been discussed by Sajid *et al.* [41]. The same method presented in [40] is adopted here for solving the highly non-linear boundary value problems.

#### **Mathematical formulation**

The boundary-layer flow of viscoelastic Walter-B fluid is governed [40]:

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \tag{1}$$

$$u\frac{\partial u}{\partial x} + v\frac{\partial u}{\partial y} = -\frac{1}{\rho}\frac{\mathrm{d}P}{\mathrm{d}x} + \frac{\mu_0}{\rho}\left(\frac{\partial^2 u}{\partial y^2}\right) - \frac{k_0}{\rho}\left[u\frac{\partial^3 u}{\partial x\partial y^2} - \frac{\partial u}{\partial y}\frac{\partial^2 u}{\partial x\partial y} + v\frac{\partial^3 u}{\partial y^3} + \frac{\partial u}{\partial x}\frac{\partial^2 u}{\partial y^2}\right]$$
(2)

where u and v are, respectively, the horizontal and vertical velocity components,  $\rho$  – the density, P – the pressure,  $\mu_0$  and  $k_0$  are coefficient of viscosity and viscoelastic parameter, respectively.

The energy equation with heat source/sink and radiations is given:

$$\rho c_p \left( u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} \right) = k_1 \frac{\partial^2 T}{\partial y^2} - \frac{\partial q_r}{\partial y} + Q \left( T - T_{\infty} \right)$$
(3)

in which T and  $T_{\infty}$  are the fluid and free stream temperatures, respectively. Furthermore,  $c_p$ ,  $k_1$ , Q, and  $q_r$  denote the specific heat, thermal conductivity, volumetric rate of heat absorption/generation, and radiative heat flux, respectively. Employing Rosseland approximations [42], we can write:

$$q_r = -\frac{4\sigma^*}{3k^*} \frac{\partial T^4}{\partial y} \tag{4}$$

where  $k^*$  and  $\sigma^*$  are, respectively, the mean absorption coefficient and Stefan-Boltzmann constant. Following Bataller [42],  $T^4$  can be expressed using Taylor series:

$$T^4 \cong 4T_{\infty}^3 T - 3T_{\infty}^4 \tag{5}$$

Using eqs. (4) and (5), eq. (3) implies:

$$\rho c_p \left( u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} \right) = \left( k_1 + \frac{16\sigma^* T_\infty^3}{3k^*} \right) \frac{\partial^2 T}{\partial y^2} + Q \left( T - T_\infty \right)$$
(6)

We are aiming to discuss the Blasius, Sakiadis, and stagnation point flows. Boundary conditions for the considered flow situations for Blasius and stagnation point flows:

$$u(0) = v(0) = 0, \ T(0) = T_w, \ u(\infty) = U_\infty, \ T(\infty) = T_\infty$$
(7)

and for Sakiadis flow boundary conditions:

$$u(0) = U_w, v(0) = 0, T(0) = T_w, u(\infty) = 0, T(\infty) = T_{\infty}$$
 (8)

in which  $U_{\infty}$  and  $U_{w}$  are, respectively, the free stream and wall velocities. Furthermore, free stream velocity for the stagnation point flow is  $U_{\infty} = ax$ . Also  $T_{w}$  is the surface temperature.

Equation (2) can be transformed to ODE by a choice of suitable transformations [42]:

$$\psi = \sqrt{v x U_{\infty}} f(\eta), \quad \eta = \sqrt{\frac{U_{\infty}}{v x y}}, \quad \theta(\eta) = \frac{T - T_{\infty}}{T_{w} - T_{\infty}}$$
(9)

such that  $\partial \psi / \partial y = u$  and  $-\partial \psi / \partial x = v$ .

Therefore, in the transformed variables we have:

$$f''' + \frac{1}{2}ff'' + K\left(ff^{iv} + 2ff''' - f''^{2}\right) = 0 \qquad \text{for Blasius and Sakiadis flow}$$
(10)

$$f''' + ff'' - f^{2} + 1 + K \left( ff^{iv} - 2ff''' + f''^{2} \right) = 0 \quad \text{for stagnation point flow}$$
(11)

where  $K = k_0 U_{\infty}/2\mu x$  denotes the local Weissenberg number in the case of Blasius and Sakiadis flows and is a constant Weissenberg number for stagnation point flow. Energy equation in transformed co-ordinates takes the form:

$$\theta'' + \Pr_{\text{eff}}\left(\frac{1}{2}f\theta' + \lambda\theta\right) = 0$$
 (for Blasius and Sakiadis flow) (12)

$$\theta'' + \Pr_{\text{eff}}(f\theta' + \lambda\theta) = 0$$
 (for stagnation point flow) (13)

in which  $Pr_{eff} = Pr/(1 + Nr)$  denotes the effective Prandtl number as discussed by [39],  $Nr = 16\sigma^*T_{\infty}^3/3k^*k_1$  represents radiation parameter and  $\lambda = Qx/\rho c_p U_{\infty}$  the heat sink ( $\lambda < 0$ ) or source ( $\lambda > 0$ ) parameter. Boundary conditions for the considered flow problems:

$$f(0) = f'(0) = 0, \ \theta(0) = 1, \ f'(\infty) = 1, \ \theta(\infty) = 0 \qquad \text{(for Blasius and stagnation flow)} \tag{14}$$

$$f(0) = 0, f'(0) = 1, \theta(0) = 1, f'(\infty) = 0, \theta(\infty) = 0 \quad \text{(for Sakiadis flow)}$$
(15)

#### Numerical solutions

In this section we briefly explain the numerical technique known as legendre wavelet spectral collocation method (LWSCM) [41] used to solve the considered problems. In the first step eqs. (10) and (12) are converted into initial value problems via shooting method. Letting f''(0) = s and  $\theta'(0) = s_1$ , and differentiating eq. (10) w.r.t. *s* and eq. (12) w.r.t.  $s_1$  along with their boundary conditions:

$$g''' + \frac{1}{2}gf'' + \frac{1}{2}fg'' + K\left(gf^{iv} + fg^{iv} + 2fg''' + 2g'f''' - 2f'g''\right) = 0$$
(16)

$$t'' + \Pr_{\text{eff}}\left(\frac{1}{2}ft' + \lambda t\right) = 0$$
(17)

$$g(0) = 0, g'(0) = 0, g''(0) = 1, t(0) = 0, t'(0) = 1$$
 (18)

1277

In the next step the domain  $0 \le \eta < \eta_{\infty}$  is divided into subintervals  $[(n-1)/2^{k-1}, n/2^{k-1}]$  in which  $n = 1, \dots 2^{k-1}\eta_{\infty}$ . Therefore:

$$\chi_{lj}\left(\eta\right) = 0 \text{ for any } l \neq n \text{ and } \eta \in \left\lfloor \frac{n-1}{2^{k-1}}, \frac{n}{2^{k-1}} \right)$$
(19)

where

$$\chi_{lj}(\eta) = \left\{ \begin{pmatrix} m+\frac{1}{2} \end{pmatrix}^{\frac{1}{2}} 2^{\frac{k}{2}} L_m \left( 2^k \eta - 2n + 1 \right), \frac{n-1}{2^{k-1}} \le \eta < \frac{n}{2^{k-1}} \\ 0, \text{ otherwise} \end{cases} \right\}$$

are discrete wavelets in which  $k = 1, 2, ..., \eta_{\infty}$ ,  $n = 1, 2, ..., 2^{k-1}\eta_{\infty}$ . Legendre wavelet interpolation approximation the functions  $f(\eta)$  and  $\theta(\eta)$  on the  $n^{\text{th}}$  subinterval is given:

$$f(\eta) \simeq F_n(\eta) = \sum_{l=1}^{2^{k-1}} \sum_{j=0}^{M-1} I_{j}(\eta) f_{j} = \sum_{j=0}^{M-1} I_{nj}(\eta) y_{nj}, \text{ for } \eta \in \left[\frac{n-1}{2^{k-1}}, \frac{n}{2^{k-1}}\right]$$
(20)

$$\theta(\eta) \simeq \theta_n(\eta) = \sum_{l=1}^{2^{k-1}} \sum_{j=0}^{M-1} I_{j}(\eta) \theta_{j} = \sum_{j=0}^{M-1} I_{nj}(\eta) \theta_{nj}, \text{ for } \eta \in \left[\frac{n-1}{2^{k-1}}, \frac{n}{2^{k-1}}\right]$$
(21)

Similarly, one can define:

$$g(\eta) \simeq G_n(\eta) = \sum_{j=0}^{M-1} I_{nj}(\eta) g_{nj}, \ t(\eta) \simeq T_n(\eta) = \sum_{j=0}^{M-1} I_{nj}(\eta) t_{nj}$$
(22)

where

$$I_{nj}(\eta) = \overline{w}_j \sum \chi_{n,m}(x_{nj}) \psi_{n,m}(\eta), \quad j = 0, \dots, M-1, \quad n = 1, \dots, 2 \quad \eta_{\infty}$$
(23)

and

$$\overline{w}_j = \frac{w_j}{2^k}, \quad x_{nj} = \frac{x_j}{2^k} + \frac{2n-1}{2^k}, \quad j = 0, \dots, M-1, \quad n = 1, \dots, 2^{k-1} \eta_{\infty}$$
(24)

$$w_{j} = \frac{2}{\left(1 - x_{j}^{2}\right) \left[L'_{M}\left(x_{j}\right)\right]^{2}}, \quad j = 0, 1, \dots, M - 1$$
(25)

where  $x_j$  are the Legendre-Gauss collocation points and  $w_j$  the corresponding weights. In fact,  $x_j$  are the roots of  $L_m(x)$  in the interval (-1, 1) arranged in ascending order. Applying the points  $\{x_{nj}|n=1,...,2^{k-1}\eta_{\infty}, j=3,..., M-1\}$  into governing initial value problems:

$$F_n''' + \frac{1}{2}F_nF_n'' + K\left(F_nF_n^{i\nu} + 2F_n'F_n'' - F_n''^2\right) = 0$$
(26)

$$G_n'' + \frac{1}{2}G_nF_n'' + \frac{1}{2}F_nG_n'' + K\left(G_nF_n^{i\nu} + F_nG_n^{i\nu} + 2F_n'G_n''' + 2G_n'F_n''' - 2F_n''G_n'''\right) = 0$$
(27)

$$\theta_n'' + \Pr_{\text{eff}}\left(\frac{1}{2}F_n\theta_n' + \lambda\theta_n\right) = 0$$
<sup>(28)</sup>

$$T_n'' + \Pr_{\text{eff}}\left(\frac{1}{2}F_nT_n' + \lambda T_n\right) = 0$$
<sup>(29)</sup>

$$F_1(0) = 0, \quad F_1'(0) = 0, \quad F_1''(0) = s, \quad \theta_1(0) = 1, \quad \theta_1'(0) = s_1$$
(30)

$$G_1(0) = 0, \quad G'_1(0) = 0, \quad G''_1(0) = 1, \quad T_1(0) = 0, \quad T'_1(0) = 1$$
 (31)

The initial value problems (26)-(31) are solved using parallel shooting technique in which solutions in the preceding subinterval provides the initial conditions for the next subinterval. The values of s and  $s_1$  are modified using Newton's method so that  $F_{2^{k-1}\eta_{\infty}}(\eta_{\infty})$ , = 1,  $\theta_{2^{k-1}\eta_{\infty}}(\eta_{\infty})$ , = 0. The appropriate values of M and k are chosen to obtain an accuracy of  $10^{-6}$ . Sakiadis and stagnation point flow problems can be solved in the same way.

## Numerical results and discussion

The mathematical models developed for analysis of heat transfer in Blasius, Sakiadis, and stagnation point flows are solved numerically by implementing LWSCM technique. To ensure that the obtained solutions are convergent and accurate residual errors in all the cases have been plotted in fig.1. The figure elaborates that the obtained solutions are within an accuracy of  $10^{-6}$ .



Variation in the fluid temperature,  $\theta$ , against the physical parameters is illustrated in figs. 2-4. Our main attention is focused to see the influence of  $Pr_{eff}$ ,  $\lambda$ , and K on the fluid temperature,  $\theta$ , inside the boundary-layer. Effects of Weissenberg number on the  $\theta$  for the Blasius





Figure 2. Influence of Weissenberg number on the temperature for (a) Blasius flow, (b) Sakiadis flow, and (c) stagnation point flow



Figure 3. Influence of parameter  $\lambda$  on the temperature for (a) Blasius flow, (b) and Sakiadis flow, and (c) stagnation point flow



flow are displayed in fig. 2(a). This figure depicts that temperature and thermal boundary-layer thickness decrease by increasing Weissenberg number. It is concluded from fig. 2(a) that the viscoelastic nature of the fluid reduces the temperature. The similar observation is noted in the case of Sakiadis and stagnation point flows, see figs. 2(b) and 2(c).

Figure 3 depicts an increase/decrease in the temperature and thermal boundary-layer thickness with heat source/sink in all the three considered flow situations.

Variation in the temperature against the effective Prandtl number,  $Pr_{eff}$ , is elaborated in fig. 4. According to this figure, fluid temperature and thermal boundary-layer thickness decrease with an increase in  $Pr_{eff}$ . This decrease in the value of  $\theta$  is due to the fact that  $Pr_{eff}$  is directly proportional to the Prandtl number and inversely proportional to the radiation parameter.

To analyze the surface heat transfer rate against  $Pr_{eff}$  and  $\lambda$ , tabs. 1-3 have been plotted for Blasius, stagnation point, and Sakiadis flows. This table shows that heat transfer rate increases by increasing heat source and decreases by increasing heat sink. The table also depicts that heat transfer rate increases by increasing  $Pr_{eff}$ . Similar behavior is noted in tabs. 2 and 3 for the Sakiadis and stagnation point flows.

Pr <sub>eff</sub>	$\lambda = -0.3$	$\lambda = -0.2$	$\lambda = 0$	$\lambda = 0.05$	$\lambda = 0.2$
0.7	-0.508088	-0.441539	-0.280936	-0.232344	-0.051440
1	-0.598573	-0.516683	-0.315068	-0.252399	-0.007691

Table 1. Variation in  $\theta'(0)$  against Pr<sub>eff</sub> and  $\lambda$  for Blasius flow when K = 0.2

Iqbal, S. A., et al.: An Iterative Approach to Viscoelastic Boundary Layer ... THERMAL SCIENCE: Year 2020, Vol. 24, No. 2B pp. 1275-1284

	(, ) 0		<u> </u>		
Pr <sub>eff</sub>	$\lambda = -5$	$\lambda = -1$	$\lambda = 0$	$\lambda = 0.1$	
0.7	-1.898130	-0.948779	-0.560127	-0.513127	
1	-2.264172	-1.112076	-0.614666	-0.551946	
5	-5.031365	-2.372691	-1.076984	-0.890872	
10	-7.103287	-3.308321	-1.383130	-1.092058	

Table 2. Variation in  $\theta'(0)$  against  $Pr_{eff}$  and  $\lambda$  for stagnation point flow when K = 0.1

Table 3. Variation in  $\theta'(0)$  against  $Pr_{eff}$  and  $\lambda$  for Sakiadis flow when K = 0.2

Pr <sub>eff</sub>	$\lambda = -0.05$	$\lambda = -0.01$	$\lambda = 0$	$\lambda = 0.05$	$\lambda = 0.1$
0.7	-0.397338	-0.356621	-0.345555	-0.283274	-0.202051
1	-0.495604	-0.450697	-0.438551	-0.371873	-0288115
3	-0.941025	-0.879018	-0.862491	-0.775317	-0.679052
5	-1.249001	-1.171096	-1.150972	-1.045640	-0.931322
10	-1.809997	-1.704664	-1.67702	-1.536881	-1.385855

## Conclusion

In this study, we have applied an iterative approach based on the LWSCM to present a boundary-layer analysis for the heat transfer in a Walter-B viscoelastic fluid for three cases namely Blasius, Sakiadis, and stagnation point flows. Numerical solutions are obtained to discuss heat transfer characteristics during the flow. The results are given for temperature distribution for the influence of various pertinent parameters. It is found that the temperature of the fluid is decreased for the Weissenberg and Prandtl numbers. Also it is noticed that the proposed algorithm is very efficient and one can apply it on various flow problems regarding in non-Newtonian fluids.

## Acknowledgment

We are thankful to the reviewers for their encouraging comments and constructive suggestions to improve the quality of the manuscript.

## References

- Blasius, H., Grenzschichten in Flussigkeitenmitkleiner Reibung, Z. Angew Math. Phys., 56 (1908), pp. 1-37
- Sakiadis, B. C., Boundary-Layer Behavior on Continuous Solid Surfaces I: BoundaryLayer Equations for 2-D and Axisymmetric Flow, *AIChE J.*, 7 (1961), 1, pp. 26-28
- [3] Sakiadis, B. C., Boundary-Layer Behavior on Continuous Solid Surface II: Boundary-Layer on a Continuous Flat Surface, AIChE. J., 7 (1961), 2, pp. 221-225
- [4] Crane, L. J., Flow Past a Stretching Plate, Z. Angew Math. Phys., 21 (1970), July, pp. 645-647
- [5] Gupta, P. S., Gupta, A. S., Heat and Mass Transfer on a Stretching Sheet with Suction or blowing, Journal Chem. Eng., 55 (1977), 6, pp. 744-748
- [6] Vleggar, J., Laminar Boundary-Layer Behaviour on Continuous, Accelerating Surfaces, Chem. Eng. Sci., 32 (1977), 12, pp. 1517-1525
- [7] Tsou, F. K., et al., Flow and Heat Transfer in the Boundary-Layer on a Continuous Moving Surface, Int. J. Heat Mass Transf., 10 (1967), 2, pp. 219-235
- [8] Takhar, H. S., et al., Boundary-Layer Flow Due to a Moving Plate: Variable Fluid Properties, Acta Mech., 90 (1991), Mar., pp. 37-42
- [9] Hiemenz, K., Die Grenzschicht an einem in den gleichförmigen Flüssigkeitsstrom eingetauchten geraden Kreiszylinder (in German), *Dingler's Polytech. J.*, 326 (1911), pp. 321-410

Iqbal, S. A., *et al.*: An Iterative Approach to Viscoelastic Boundary Layer ... THERMAL SCIENCE: Year 2020, Vol. 24, No. 2B, pp. 1275-1284

- [10] Cortell, R., Effects of Viscous Dissipation and Work Done by Deformation on the MHD Flow and Heat Transfer of a Viscoelastic Fluid over a Stretching Sheet, *Phys. Lett. A*, 357 (2006), 4-5, pp. 298-305
- [11] Cortell, R., A Note on Flow and Heat Transfer of a Viscoelastic Fluid over a Stretching Sheet, Int. J. Non-Linear Mech., 41 (2006), 1, pp. 78-85
- [12] Abbas, Z., et al., Analytical Investigation of Maxwell Fluid-Flow with Radiation in an Axisymmetric Semi-Porous Channel by Parameterized Perturbation Method, Journal Brazilian Soci. Mech. Sci. Engng., 40 (2018), Jan., 65
- [13] Abbas, Z., et al., Analysis of Eyring Powell Liquid-Flow in Curved Channel with Cattaneo-Christove Heat Flux Model, Journal Brazilian Soci. Mech. Sci. Engng., 40 (2018), July, 390
- [14] Sheikholeslami, M., Zeeshan A., Analysis of flow and Heat Transfer in Water Based Nanofluid Due to Magnetic Field in a Porous Enclosure with Constant Heat Flux Using CVFEM, Imulation of Water Based Nanofluid Convective Flow Inside a Porous Enclosure Via Non-Equilibrium Model, *Comput. Methd. Appl. Mech. Engng*, 320 (2017), pp. 68-81
- [15] Sadeghy, K., et al., Sakiadis Flow of an Upper-Convected Maxwell Fluid, Int. J. Non-Linear Mech., 40 (2005), 9, pp. 1220-1228
- [16] Liu, I. C., Flow and Heat Transfer of an Electrically Conducting Fluid of Second Grade in a Porous Medium over a Stretching Sheet Subject to a Transverse Magnetic Field, *Int. J. Non-Linear Mech.*, 40 (2005), 4, pp. 465-474
- [17] Ariel, P. D., et al., The Flow of an Elastico-Viscous Fluid Past a Stretching Sheet with Partial Slip, Acta Mech., 187 (2006), Aug., pp. 29-35
- [18] Liao, S. J., Campo, A., Analytic Solutions of the Temperature Distribution in Blasius Viscous Flow Problems, *Journal Fluid Mech.*, 453 (2002), Feb., pp. 411-425
- [19] Liao, S. J., On the Analytic Solution of Magnetohydrodynamic Flows of Non-Newtonian Fluid over a Stretching Sheet, *Journal Fluid Mech.*, 488 (2003), July, pp. 189-212
- [20] Xu, H. S., Liao, J., Series Solutions of Unsteady Magnetohydrodynamic Flows of Non-Newtonian Fluids Caused by an Impulsively Stretching Plate, *Journal Non-Newton. Fluid Mech.*, 129 (2005), 1, pp. 46-55
- [21] Hayat, T., et al., Series Solution for the Upper-Convected Maxwell Fluid over a Porous Sretching Plate, Phys. Lett. A, 358 (2006), 5-6, pp. 396-403
- [22] Hayat, T., Sajid, M., Analytic Solution for Axisymmetric Flow and Heat Transfer of a Second Grade Fluid Past a Stretching Sheet, Int. J. Heat Mass Transf., 50 (2007), 1-2, pp. 75-84
- [23] Cortell, R., Effects of Viscous Dissipation and Radiation on the Thermal Boundary-Layer over a Non-Linearly Stretching Sheet, *Phys. Lett. A*, 372 (2008), 5, pp. 631-636
- [24] Cortell, R., Radiation Effects in the Blasius Flow, Appl. Math. Comp., 198 (2000), 1, pp. 333-338
- [25] Cortell, R., Effects of Heat Source/Sink, Radiation and Work Done by Deformation on fFow and Heat Transfer of a Viscoelastic Fluid over a Stretching Sheet, *Comput. Math. Appl.*, 53 (2007), pp. 305-316
- [26] Cortell, R., Similarity Solutions for Boundary-Layer Flow and Heat Transfer of a FENE-P Fluid with Thermal Radiation, *Phys. Lett. A*, 372 (2008), pp. 2431-2439
- [27] Sheikholeslami, M., et al., Numerical Modelling for Alumina Nanofluid Magnetohydrodynamics Convective Heat Transfer in a Permeable Medium Using Darcy Law, Int. J. Heat Mass Transf., 127 (2018), pp. 614-622
- [28] Naveed, M., et al., Thermophoresis and Brownian Effects on the Blasius Flow of a Nanofluid Due to a Curved Surface with Thermal Radiation, Eur. Phys. J. Plus, 131 (2016), 214
- [29] Sajid, M., Hayat, T., Influence of Thermal Radiation on the Boundary-Layer Flow Due to an Exponentially Stretching Sheet, Int. Comm. Heat Mass Transf., 35 (2008), 3, pp. 347-356
- [30] Ariel, P. D., Flow of Viscoelastic Fluids through a Porous Channel-I, Int. J. Numer. Meth. Fluids, 17 (1993), 7, pp. 605-633
- [31] Ariel, P. D., A New Finite-Difference Algorithm for Computing the Boundary-Layer Flow of Viscoelastic Fluids in Hydromagnetics, *Comput. Meth. Appl. Mech. Eng.*, 124 (1995), 1-2, pp. 1-13
- [32] Ariel, P. D., On Extra Boundary Condition in the Stagnation Point Flow of a Second Grade Fluid, Int. J. Eng. Sci., 40 (2002), 2, pp. 145-162
- [33] Sadeghy, K., Sharifi, M., Local Similarity Solution for the Flow of a Second Grade Viscoelastic Fluid Above a Moving Plate, *Int. J. Non-Linear Mech.*, 39 (2004), 8, pp. 1265-1273
- [34] Sajid, M., et al., Boundary-Layer Flow of an Oldroyd-B Fluid in the Region of Stagnation Point over a Stretching Sheet, Can. J. Phys., 88 (2010), 9, pp. 635-640
- [35] Hayat, T., et al., Effect of Heat Transfer on the Flow of a Second Grade Fluid in Divergent/Convergent Channel, Int. J. Numer. Meth. Fluids, 64 (2010), 7, pp. 761-776

- [36] Sajid, M., Effects of Permeability on Swimming of a Micro-Organism in an Oldroyd-B Fluid, Journal Porous Media, 17 (2014), 1, pp. 59-66
- [37] Raptis, A., Perdikis, C., Viscoelastic Flow by the Presence of Radiation, ZAMM, 78 (1998), 4, pp. 277-279
- [38] Seddeek, M. A., Effects of Radiation and Variable Viscosity on a MHD Free Convection Flow Past a Semi-Infinite Flat Plate with an Aligned Magnetic Field in the Case of Unsteady Flow, *Int. J. Heat Mass Transf.*, 45 (2002), 4, pp. 931-935
- [39] Raptis, A., Effect of Thermal Radiation on MHD Flow, Appl. Math. Comput., 153 (2004), 3, pp. 645-649
- [40] Beard, D. W., Walters, K., Elastico-Viscous Boundary-Layer Flows I, 2-D Flow Near a Stagnation Point, Proc. Camb. Phil. Soc., 60 (1964), 3, pp. 667-674
- [41] Sajid., M., et al., A Legendre Wavelet Spectral Collocation Technique Resolving Anomalies Associated with Velocity in Some Boundary-Layer Flows of Walter-B liquid, Meccanica, 52 (2016), Apr., pp. 877-887
- [42] Bataller, R. C., Radiation Effects for the Blasius and Sakiadis Flows with a Convective Surface Boundary condition, *Appl. Math. Comp.*, 206 (2008), 2, pp. 832-840