MECHANICAL CHARACTERIZATION OF FRACTURED GRANITE RESERVOIRS

by

Xiongdi ZUO^{*a,b*}, Liangbin DOU^{*a,b*}, Hongjiang ZOU^{*c,d*}, Ming ZHANG^{*a,b*}, Tiantai LI^{*a,b**}, and Xiaogang SHI^{*e*}

^a College of Petroleum Engineering, Xi'an Shiyou University, Xi'an, China
 ^b Engineering Research Center of Development and Management for
 Western Low to Extra-Low Permeability Oilfield, Xi'an Shiyou University, Xi'an, China
 ^c Drilling and Production Engineering Technology Institute,
 Chuanqing Drilling Engineering Company Limited, CNPC, Xi'an, China
 ^d National Engineering Laboratory for Exploration and Development of
 Low Permeability Oil and Gas Fields, Xi'an, China
 ^e Engineering Technology Research Institute of XEDC, Karamay, China

Original scientific paper https://doi.org/10.2298/TSCI230612036Z

In this paper, on the basis of laboratory triaxial mechanical experiments, a granite model including different numbers and angles of fractures was established by the discrete element method. Combined with the laboratory triaxial mechanical experiments and PCF simulation results, the effects of the number and angle of fractures on the rock mechanical properties of fractured granite reservoirs were analyzed. The results show that the existence of fractures significantly reduces the strength of the reservoir, but the increase of the fracture angle and the confining pressure will weaken the degree of this reduction, and the fractures are easy to expand and connect during the loading process.

Key words: fractured granite reservoirs, mechanical properties, discrete element method, fractures

Introduction

With the continuous growth of the requirement of oil and gas resources as well as the progress of oil and gas exploration technology, unconventional oil and gas resources have become the key field of oil and gas exploration and development, and the continuous discovery of large granite oil and gas reservoirs around the world has proved that its potential for exploration and development is very large, which has attracted more and more attention and concern from petroleum and geological fields [1]. However, the complex internal structure and the development of natural fractures and microfractures and other defects in granite reservoirs result in complex mechanical properties and damage mechanisms, which, if not understood, can cause problems such as well borehole instability and solid-phase production of reservoirs, so it is important to deeply study the mechanical characteristics and damage mechanisms of fractured granite reservoirs [2, 3]. In recent years, the mechanical properties and damage mechanism of defective rocks have been one of the hot areas for rock mechanics researchers [4]. The PFC simulation method can simulate the mechanical behavior of rocks through the movement and

^{*}Corresponding author, e-mail: ttli@xsyu.edu.cn

the fracture between particles in the model under different stress conditions, and has a better simulation effect, which has been widely used in the field of rock mechanics [5].

In this paper, on the basis of laboratory triaxial mechanical experiments, a granite model including different numbers and angles of fractures was established by the discrete element method. The effect of the number and angle of fractures on the mechanical characteristics of fractured granite reservoirs were analyzed by combining the results of the indoor triaxial mechanical experiments and PCF simulation, which can provide reference for the development and production of fractured granite reservoirs.

The indoor triaxial mechanical experiment

The granite sample used in the indoor triaxial experiment is originated from the granite submerged reservoir in Qiongdongnan Basin, with a depth range of 2969.8-3896.5 m. The main mineral component is dominated by feldspar, followed by quartz, containing some hornblende, mica and opaque minerals. The permeability is $<0.050 \times 10^{-3} \mu m^2$ and porosity is <1%. No more obvious fractures were found after CT scanning and acoustic emission testing. Considering that the scale of prefabricated fractures is larger than the microfractures existing in the rock samples themselves, it is considered that the cores sample used in the test are fracture-free granite cores.

The experiments were accomplished by using TAW-1000 microcomputer electro-hydraulic servo-controlled rock triaxial stress tester, which gradually applied axial load at a rate of 1 mm per minute until the sample was damaged, and the specific information of the test samples and the test results are shown in tab. 1. The density of the rock sample is about 2.60 g/cm³. The compressive strength is about 143.675 MPa, Young's modulus is about 44.57 Gpa, and Poisson's ratio is about 0.155.

Number	Diameter [mm]	Height [mm]	Quantity [g]	Density [gcm ³]	Compressive strength [MPa]	Young's modulus [GPa]	Poisson's ratio
1#	24.50	49.16	59.34	2.56	132.62	40.16	0.175
5#	24.65	48.65	61.40	2.64	154.73	48.98	0.135
Average	_	_	_	2.60	143.675	44.57	0.155

Table 1. The results and information of indoor experiment samples

The PFC simulation model

Based on results of indoor triaxial experiments, a PFC simulation model was formulated to simulate and analyse the mechanical characteristics of fractured granite reservoirs. The size of the numerical model is a standard rock sample with radius r = 25 mm, height h = 100 mm. The wall was randomly filled with particles with a porosity of 1%, the minimum radius of the filled particles was 0.35 mm, and the ratio of the maximum radius to the minimum radius was 2, resulting in a total number of 6268 particles. The simulated sample density was set to the average density (2600 kg/m³) of the granite tested by the indoor experiment.

The stress-strain curves and damage patterns of the rocks obtained from indoor experiments are used as references when determining microscopic mechanical parameters, and the microscopic parameters of the model are adjusted using the *trial-and-error method*, so that the simulation results are basically the same as those of the indoor experiments in terms of the stress-strain curves and damage patterns [6]. The specific microscopic parameters selected for the numerical model are shown in tab. 2. When performing the calculations, the PFC discrete element is realized by the following two principles as follows. Newton's second law reads F = ma. The relationship between force and displacement is given as $s = v_0 t + at^2/2$.

Value Value Microscopic parameters Microscopic parameters Minimum particle diameter [mm] 0.35 Friction coefficient 0.7 Ratio of particle diameter 2 Vertical bonding strength [MPa] 50 Porosity [%] 1 Tangential bonding strength [MPa] 80 2600 Parallel bonding friction angle [°] 43.68 Density [kgm-3] Parallel bonding modulus [Gpa] Contact modulus of particles [GPa] 10.5 10.5 Ratio of vertical to tangential Ratio of vertical to tangential 1.5 1.5 stiffness for particles stiffness for parallel bonding

 Table 2. The specific microscopic parameters for the numerical model

As shown in fig. 1, the model simulation results basically matched with the indoor test results in terms of stress-strain curves and damage patterns, proving the accuracy of the model mechanical parameters.



Figure 1. Comparison of simulation results and indoor experimental results; (a) comparison of damage patterns and (b) comparison of stress-strain curves

Effect of fractures on the mechanical characteristics of granite reservoirs

The effect of fracture angle

Prefabricated fractures were added to the experimental model with a fracture length of 20 mm and fracture angles of 0°, 30°, 60°, and 90°, respectively, to simulate its uniaxial compressive mechanical behavior, and the results are shown in figs. 2 and 3. The sample without prefabricated fracture started to initiate cracks at a strain of 0.208%, and the axial stress reached a compressive strength of 157.23 MPa at a strain of 0.392%, following which the cracks increased rapidly and the sample was damaged. For the prefabricated fracture samples, the crack initiation strain was earlier, the compressive strength and Young's modulus reduce, and as the angle of the prefabricated fracture increases, the strain at which cracks begin to initiate is delayed and the compressive strength and Young's modulus increase. In addition, as shown in fig. 4, with the increase of prefabricated fracture angle, the number of cracks in the sample damage is increased and the cracks are more easily connected. It indicates that prefabricated fracture angle will weaken this reduction, and the low angle fracture results in a higher damage degree to the samples.





Figure 2. Stress-strain curve of the samples with different angles prefabricated fracture



Figure 4. The cracks distribution of samples with different angles prefabricated fracture during damage; (a) 0°, (b) 30°, (c) 60°, and (d) 90°

The effect of fracture number

Multiple prefabricated fractures were added to the simulation model with a fracture length of 20 mm and a fracture angle of 90°, and the simulation results are shown in figs. 5 and 6. With the increase of the number of prefabricated fractures, the compressive strength and



Figure 5. Stress-strain curve of the samples with different numbers prefabricated fractures



Figure 6. Effect of prefabricated fracture number on the mechanical characteristics of the samples

Figure 3. Effect of prefabricated fracture angle on the mechanical characteristics of the samples

Zuo, X., *et al.*: Mechanical Characterization of Fractured Granite Reservoirs THERMAL SCIENCE: Year 2024, Vol. 28, No. 2A, pp. 1135-1140



Figure 7. The cracks distribution of samples with different numbers prefabricated fractures during damage; (a) 1 fracture, (b) 2 fractures, (c) 3 fractures, (d) 4 fractures, and (e) 5 fractures

Young's modulus of the sample gradually decreased, and the cracks began to initiate strain is earlier, indicating that with the increase of the number of fractures, the mechanical properties of the samples are significantly reduced, and the samples are more easily damaged. Figure 7 shows the distribution of cracks at damage for different numbers of prefabricated fracture samples, from which it can be seen that with the increase in the number of prefabricated fractures, the cracks are mainly concentrated in the region of prefabricated fracture distribution.

The effect of confining pressures

The mechanical behaviors of the sample without prefabricated fracture and the sample with 0° prefabricated fracture are simulated under 0 MPa, 10 MPa, 20 MPa, and 30 MPa confining pressures, respectively, and the results are shown in figs. 8 and 9, which show that the compressive strengths of the sample without prefabricated fracture and the sample with 0° prefabricated fracture are both increased with the increase of the confining pressure. From fig. 9, it can be seen that the compressive strengths of the samples with 0° prefabricated fractures are lower than those of the samples without prefabricated fractures at the same confining pressure, and the degree of reduction gradually decreases with the increase of the confining pressure, which indicates that the confining pressure will inhibit the degree of reduction of the strength of the samples by the prefabricated fractures.



Figure 8. Stress-strain curve of sample under different confining pressure; (a) the sample without prefabricated fracture and (b) the sample with 0° prefabricated fracture



compressive strength of samples

Conclusion

In this paper, on the basis of laboratory triaxial mechanical experiments, a granite model including different numbers and angles of fractures was established by the discrete element method. Combined with the laboratory triaxial mechanical experiments and PCF simulation results, the effects of the number and angle of fractures on the rock mechanical properties of fractured granite reservoirs were analyzed. The prefabricated fractures significantly reduce the compressive strength and Young's modulus of sample, and the crack initiation strain was earlier. Moreover, the increase of the fracture angle

and the confining pressure will weaken the degree of this reduction, and the low angle fracture results in a higher damage degree to the samples.

Acknowledgment

This work is supported by the Innovation Capability Support Program of Shaanxi (2022KJXX-63).

References

- Ye, T., et al., The Reservoir Characteristics And Their Significance For Deliverability In Metamorphic Granite Buried Hill: A Case Study from the JZS Oil Field in the Liaodong Bay Basin, NE China, Arabian Journal of Geosciences, 12 (2019), 20, pp. 1-9
- [2] You, L., et al., Reservoir Characteristics and Genetic Mechanisms of the Mesozoic Granite Buried Hills in the Deep-Water of the Qiongdongnan Basin, Northern South China Sea, Acta Geologica Sinica, 95 (2021), 1, pp. 259-267
- [3] Zuo, X., et al., Study on the Solid Production Mechanism of the Fractured Granite Reservoirs-Example of YL Area in Qiongdongnan Basin, Processes, 10 (2022), 12, 2556
- [4] Dou, L., et al., Study on the Effect Of High-Temperature Heat Treatment On The Microscopic Pore Structure and Mechanical Properties of Tight Sandstone, Geofluids, 2021 (2021), 2, pp. 1-13
- [5] Li, Y., et al., Particle Flow Analysis of Parallel Double Crack Evolution under Uniaxial Compression, Journal of Central South University (Science and Technology), 50 (2019), 12, pp. 3035-3045
- [6] Kunmeng, L., et al., Method to Determine Microscopic Parameters of PFC-2D Numerical Model, Journal of Northeastern University: Natural Science, 37 (2016), 4, pp. 563-567

1140